

Safety Data Sheet according to EC-Regulation 91/155/EEC

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Ultra 2040 500ml

Art.: 0890085500

Use of the substance/preparation

Refer to description of material or preparation.

Company/undertaking identification

Wurth UK Ltd 1 Centurion Way, Erith, UK-DA18 4AE Kent
Telephone 020 8319 6000, Fax 020 8319 6400

Distributor: see point 16 of this EC safety data sheet

Emergency telephone / Office for advice

Advisory office in case of poisoning:

Tel.: +49 30 / 19240 Berlin

Telephone number of the company in case of emergencies:

Tel. 020 8319 6000 (08-00 h - 18-00 h)

2. Composition/information on ingredients

Aerosol

2.1 Chemical name	content %	symbol	R-phrases	EINECS, ELINCS
Naphtha (petroleum), hydrotreated light	10 - 30	F/Xn/Xi/N	11-38-51-53-65-67	265-151-9
Naphtha (petroleum), hydrotreated light	10 - 30	Xn	10-65-66-67	265-151-9
Distillates (petroleum), hydrotreated heavy paraffinic	10 - 30			265-157-1
Isobutane	10 - 30	F+	12	200-857-2
Propane	1 - 5	F+	12	200-827-9
Butane	1 - 5	F+	12	203-448-7
Zinc alkyl dithiophosphate	< 1	N	51-53	

For complete wording of the R-phrases, refer to point 16.

3. Hazards identification

3.1 To people

See point 11 and 15.

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

Product is extremely flammable.

When using: development of explosive vapour/air mixture possible.

Irritation of the skin.

Vapours may cause drowsiness and dizziness

3.2 To the environment

See point 12.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First aid measures

4.1 Inhalation

Remove person from danger area.

GB

2 / 7

Revision: 02.05.2006 Replaces the version of: 20.11.2003 PDF date: 21.05.2007

Ultra 2040 500ml

Art.: 0890085500

Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

4.5 Special resources necessary for first aid

n.c.

5. Fire-fighting measures**5.1 Suitable extinguishing media**

Foam

CO2

Extinction powder

Cool container at risk with water.

5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon

Danger of bursting (explosion) when heated.

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply

According to size of fire

Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental measures

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

Avoid release to the environment.

6.3 Methods for cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. Handling and storage**7.1 Handling****Tips for safe handling:**

See point 6.1

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Wash hands before breaks and at end of work.

3 / 7

Revision: 02.05.2006 Replaces the version of: 20.11.2003 PDF date: 21.05.2007

Ultra 2040 500ml

Art.: 0890085500

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.2. Storage

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols.

Special storage conditions:

See point 10.2

Keep protected from direct sunlight and temperatures over 50°C.

8. Exposure controls/personal protection

Chemical Name	Naphtha (petroleum), hydrotreated light		
WEL-TWA: ** 200 ppm (1000 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Naphtha (petroleum), hydrotreated light		
WEL-TWA: ** 200 ppm (1000 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Naphtha (petroleum), hydrotreated light		
WEL-TWA: ** 200 ppm (1000 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Naphtha (petroleum), hydrotreated light		
WEL-TWA: ** 200 ppm (1000 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Distillates (petroleum), hydrotreated heavy paraffinic		
WEL-TWA: ** 70 ppm (350 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Distillates (petroleum), hydrotreated heavy paraffinic		
WEL-TWA: ** 70 ppm (350 mg/m3) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---		Other information:	---
Chemical Name	Isobutane		
WEL-TWA: ---	WEL-STEL: ---		---
BMGV: ---		Other information:	---
Chemical Name	Propane		
WEL-TWA: ---	WEL-STEL: ---		---
BMGV: ---		Other information:	---
Chemical Name	Butane		
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)		---
BMGV: ---		Other information:	---
Chemical Name	Butane		
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)		---
BMGV: ---		Other information:	---
Chemical Name	Diphenylamine		
WEL-TWA: 10 mg/m3	WEL-STEL: 20 mg/m3		---
BMGV: ---		Other information:	---
Chemical Name	Diphenylamine		
WEL-TWA: 10 mg/m3	WEL-STEL: 20 mg/m3		---
BMGV: ---		Other information:	---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(GB)

4 / 7

Revision: 02.05.2006 Replaces the version of: 20.11.2003 PDF date: 21.05.2007

Ultra 2040 500ml

Art.: 0890085500

(IR) OELV-8h = Occupational Exposure Limit Value (8-hour reference period) | OELV-15min = Occupational Exposure Limit Value (15-minute reference period) | BLV = Biological limit value | Other information: C1, C2 = carcinogenic substance, Cat. 1 or 2. Mut 1, 2 = mutagenic substance, Cat. 1 or 2. Repro 1, 2 = Substances known to be toxic for reproduction, Cat. 1 or 2. Sk = can be absorbed through skin. Asphyx = asphyxiant. Sen = Respiratory sensitizer.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Respiratory protection: Normally not necessary.

If OES or MEL is exceeded.

With short-term contact:

Filter A (EN 141)

With long-term contact:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Hand protection:

Protective nitrile gloves (EN 374)

Protective Neopren gloves (EN 374).

Protective hand cream recommended.

Eye protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

9. Physical and chemical properties

Physical state:	Aerosol
Propellant gas:	
Isobutane	
Propane	
Butane	
Colour:	White
Odour:	Characteristic
Boiling point/range (°C):	n.av.
Melting point/range (°C):	n.av.
Flash point (°C):	n.c.
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	3 bar/20°C

10. Stability and reactivity

Conditions to avoid

See point 7

Stable when handled and stored correctly.

Pressure increase will result in danger of bursting.

Pressurized container:

protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Materials to avoid

See point 7

Avoid contact with strong oxidizing agents.

Hazardous decomposition products

See point 5.3

11. Toxicological information

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	k.D.v., Irritant
Eye contact:	n.av.

Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	Possible

Further information

Classification according to calculation procedure.

The following may occur:

Irritation of the eyes

Irritant to mucosa of the nose and throat.

Nausea

Dizziness

Headaches

Effects/damages the central nervous system

12. Ecological information

Water hazard class (Germany):	Not classified
Self classification:	n.a.
Persistence and degradability:	
Not readily biodegradable *, **	
BOD 5d 33-49% ThOD, BOD 28d 53-55% ThOD **	
Behaviour in sewage plants:	n.av.
Aquatic toxicity:	
Toxicity to fish:	
LC50 10 - 100 mg/l **	
Toxicity to daphnia:	
EC50 > 100 mg/l **	
Ecological toxicity:	n.av.
* Zinc alkyl dithiophosphate	
** Naphtha (petroleum), hydrotreated light	

13. Disposal considerations

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances

20 01 99 other fractions not otherwise specified

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Residues may present a risk of explosion.

Do not perforate, cut up or weld uncleaned container.

Revision: 02.05.2006 Replaces the version of: 20.11.2003 PDF date: 21.05.2007
Ultra 2040 500ml
Art.: 0890085500

14. Transport information

General statements

UN-Number: 1950

Road/Rail-transport (ADR/RID)

Class/packing-group: 2/-

UN 1950 AEROSOLS

Classification code: 5F

LQ: 2



Transport by sea

IMDG-code: 2.1/- (class/packing-group)

EmS: F-D, S-U

Marine Pollutant: n.a.

AEROSOLS



Transport by air

IATA: 2.1/-/ (class/secondary danger/packing-group)

Aerosols, flammable

Additional information:

Danger code and packing code on request.

15. Regulatory information

Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)



Symbols: F+/Xi

Indications of danger:

Extremely flammable

Irritant

R-phrases:

12 Extremely flammable.

38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

16 Keep away from sources of ignition - No smoking.

23.c Do not breathe spray.

24 Avoid contact with skin.

35 This material and its container must be disposed of in a safe way.

51 Use only in well-ventilated areas.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Additions:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Observe restrictions: Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany): 2 B

Revised points: 8

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 2).

11 Highly flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

GB

7 / 7

Revision: 02.05.2006 Replaces the version of: 20.11.2003 PDF date: 21.05.2007

Ultra 2040 500ml

Art.: 0890085500

65 Harmful: may cause lung damage if swallowed.
65 Also harmful: may cause lung damage if swallowed.
67 Vapours may cause drowsiness and dizziness.
10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
12 Extremely flammable.

Winzer Würth Industrial Lt.
Würth House
Catteshall Lane
GB - Godalming / Surrey
GU7 1NP
Tel: 01483 412800
Fax: 01483 412805

Würth Ireland Ltd.
Monaclooe Industrial Estate
Ballysimon Road
GB - Limerick / Ireland
Tel: +353 61 430200
Fax: +353 61 430200

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40
AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.