

1 / 7

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007

Air Intake Cleaner 500ml

Art.:1893500

Safety Data Sheet according to EC-Regulation 91/155/EEC

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Air Intake Cleaner 500ml

Art.:1893500

Use of the substance/preparation

For the safe removal of gum deposits and to enhance starting properties

Company/undertaking identification

Wurth UK Ltd 1 Centurion Way, Erith, UK-DA18 4AE Kent
Telephone 020 8319 6000, Fax 020 8319 6400

Distributor: see point 16 of this EC safety data sheet

Emergency telephone / Office for advice

Advisory office in case of poisoning:

Tel.: +49 30 / 19240 Berlin

Telephone number of the company in case of emergencies:

Tel. 020 8319 6000 (08-00 h - 18-00 h)

2. Composition/information on ingredients

2.1 Chemical name	content %	symbol	R-phrases	EINECS, ELINCS
Naphtha (petroleum), hydrodesulfurized heavy	30 - 40	Xn/N	10-51-53-65-66	265-185-4
Petroleum gases, liquified	20 - 40	F+	12	270-704-2
Acetone	10 - 20	F/Xi	11-36-66-67	200-662-2
Xylene	1 -< 12,5	Xn/Xi	10-20/21-38	215-535-7
4-hydroxy-4-methyl-pentan-2-one	1 -< 10	Xi	36	204-626-7
Isononylphenol ethoxylates	1 -< 5	Xn/Xi	22-41-53	

For complete wording of the R-phrases, refer to point 16.

3. Hazards identification

3.1 To people

See point 11 and 15.

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

Product is extremely flammable.

Danger of bursting (explosion) when heated.

When using: development of explosive vapour/air mixture possible.

Irritation of the eyes

Vapours may cause drowsiness and dizziness

3.2 To the environment

See point 12.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First aid measures

4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

GB

2 / 7

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007

Air Intake Cleaner 500ml

Art.:1893500

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.3 Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

4.5 Special resources necessary for first aid

n.c.

5. Fire-fighting measures

5.1 Suitable extinguishing media

Foam

Dry extinguisher

CO2

Water jet spray

Cool container at risk with water.

5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Explosive vapour/air mixture

Danger of bursting (explosion) when heated.

5.4 Special protective equipment for fire-fighters

According to size of fire

Protective respirator with independent air supply

Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental measures

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

Avoid release to the environment.

6.3 Methods for cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. Handling and storage

7.1 Handling

Tips for safe handling:

See point 6.1

Ensure good ventilation.

(GB)

3 / 7

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007

Air Intake Cleaner 500ml

Art.:1893500

Keep away from sources of ignition - Do not smoke.
 General hygiene measures for the handling of chemicals are applicable.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.2. Storage

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.
 Observe special regulations for aerosols.

Special storage conditions:

See point 10.2

Keep protected from direct sunlight and temperatures over 50°C.

8. Exposure controls/personal protection

(GB) Chemical Name	Naphtha (petroleum), hydrodesulfurized heavy		
WEL-TWA: ** 170 ppm (600 mg/m ³) (AGW)	WEL-STEL: ** 4 (AGW)		---
BMGV: ---	Other information: ---		
(GB) Chemical Name	Petroleum gases, liquified		
WEL-TWA: 1000 ppm (1750 mg/m ³) (Liquefied petroleum gas (LPG))	WEL-STEL: 1250 ppm (2180 mg/m ³) (Liquefied petroleum gas (LPG))		---
BMGV: ---	Other information: ---		
(GB) Chemical Name	Acetone		
WEL-TWA: 500 ppm (1210 mg/m ³) (WEL, EC)	WEL-STEL: 1500 ppm (3620 mg/m ³) (WEL)		---
BMGV: ---	Other information: ---		
(GB) Chemical Name	Xylene		
WEL-TWA: 50 ppm (220 mg/m ³) (WEL), 50 ppm (221 mg/m ³) (EC)	WEL-STEL: 100 ppm (441 mg/m ³) (WEL), 100 ppm (442 mg/m ³) (EC)		---
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)		
(GB) Chemical Name	4-hydroxy-4-methyl-pentan-2-one		
WEL-TWA: 50 ppm (241 mg/m ³)	WEL-STEL: 75 ppm (362 mg/m ³)		---
BMGV: ---	Other information: ---		

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter AX P3 (EN 141)

Filter A P 3 (EN 141)

Hand protection:

Solvent resistant protective gloves (EN 374).

Protective nitrile gloves (EN 374)

Protective hand cream recommended.

Eye protection:

Normally not necessary.

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

GB

4 / 7

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007

Air Intake Cleaner 500ml

Art.:1893500

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

9. Physical and chemical properties

Physical state:	Aerosol
Propellant gas:	
Petroleum gases, liquified	
Colour:	Colourless
Odour:	Characteristic
pH-value undiluted:	n.av.
Boiling point/range (°C):	n.av.
Melting point/range (°C):	n.av.
Flash point (°C):	< 0 *
Flammability (solid/gas):	Yes
Vapour pressure:	2 bar (20°C)
Density (g/ml):	0,71
Solubility in water:	Insoluble
Viscosity:	n.c.
* Petroleum gases, liquified	

10. Stability and reactivity

Conditions to avoid

See point 7

Pressure increase will result in danger of bursting.

Pressurized container:

protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Materials to avoid

See point 7

Avoid contact with oxidizing agents.

Avoid contact with other chemicals.

Hazardous decomposition products

See point 5.3

11. Toxicological information

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	k.D.v., See point 15.
Skin contact, LD50 rat dermal (mg/kg):	k.D.v.
Eye contact:	Irritant

Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	Possible

Further information

Classification according to calculation procedure.

The following may occur:

Repeated exposure may cause skin dryness or cracking.

At high concentrations:

Product is dangerous to health.

Ingestion of large quantities:

Product is dangerous to health.

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007
Air Intake Cleaner 500ml
Art.:1893500

12. Ecological information

Water hazard class (Germany):	2
Self classification:	Yes (VwVwS)
Persistence and degradability:	n.av.
Not readily biodegradable *,**	
Behaviour in sewage plants:	n.av.
According to the recipe, contains no AOX.	
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.
* Naphtha (petroleum), hydrodesulfurized heavy	
** Isononylphenol ethoxylates	

13. Disposal considerations

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
16 05 04 gases in pressure containers (including halons) containing dangerous substances
Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Do not perforate, cut up or weld uncleaned container.

14. Transport information

General statements

UN-Number: 1950

Road/Rail-transport (ADR/RID)

Class/packing-group: 2/-

UN 1950 AEROSOLS

Classification code: 5F

LQ: 2

Transport by sea

IMDG-code: 2.1/- (class/packing-group)

EmS: F-D, S-U

Marine Pollutant: n.a.

AEROSOLS

Transport by air

IATA: 2.1/-/ (class/secondary danger/packing-group)

Aerosols, flammable

Additional information:

Danger code and packing code on request.

15. Regulatory information

**Classification according to Dangerous Product Regulations incl. EC Directives
(67/548/EEC and 1999/45/EC)**

GB

6 / 7

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007

Air Intake Cleaner 500ml

Art.:1893500



Symbols: F+/Xi/N

Indications of danger:

Extremely flammable

Irritant

Dangerous for the environment

R-phrases:

12 Extremely flammable.

36 Irritating to eyes.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

23.c Do not breathe spray.

24 Avoid contact with skin.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

29/35 Do not empty into drains; dispose of this material and its container in a safe way.

51 Use only in well-ventilated areas.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Additions: n.a.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Without adequate ventilation, formation of explosive mixtures may be possible.

Observe restrictions: Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

VOC-CH 99%

16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany):

2 B

Revised points:

8

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 2).

10 Flammable.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

65 Also harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

12 Extremely flammable.

11 Highly flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

22 Harmful if swallowed.

41 Risk of serious damage to eyes.

Winzer Würth Industrial Lt.

Würth House

Catteshall Lane

GB - Godalming / Surrey

GU7 1NP

Tel: 01483 412800

Fax: 01483 412805

Würth Ireland Ltd.

Monaclinoe Industrial Estate

Ballysimon Road

GB - Limerick / Ireland

Tel:+353 61 430200

Fax: +353 61 430200

Legend:

Revision: 10.03.2004 Replaces the version of: 11.11.2003 PDF date: 21.05.2007
Air Intake Cleaner 500ml
Art.:1893500

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked
WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40
AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)
VbF = Regulations for flammable liquids (Austria)
WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water
VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds
VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

**Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-
CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.