

1 / 7

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007

Helmet & Visor Cleaner 500ml

Art.: 500107

Safety Data Sheet according to EC-Regulation 91/155/EEC

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Helmet & Visor Cleaner 500ml

Art.: 500107

Use of the substance/preparation

Refer to description of material or preparation.

Company/undertaking identification

Wurth UK Ltd 1 Centurion Way, Erith, UK-DA18 4AE Kent
Telephone 020 8319 6000, Fax 020 8319 6400

Distributor: see point 16 of this EC safety data sheet

Emergency telephone / Office for advice

Advisory office in case of poisoning:

Tel.: +49 30 / 19240 Berlin

Telephone number of the company in case of emergencies:

Tel. 020 8319 6000 (08-00 h - 18-00 h)

REGULATION (EC) No 648/2004

5 % or over but less than 15 %
aliphatic hydrocarbons

2. Composition/information on ingredients

2.1 Chemical name	content %	symbol	R-phrases	EINECS, ELINCS
Ammonia	0,1 -< 1	C/N	34-50	215-647-6
Propan-2-ol	1 -< 15	F/Xi	11-36-67	200-661-7

For complete wording of the R-phrases, refer to point 16.

3. Hazards identification

3.1 To people

See point 11 and 15.

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

Product is extremely flammable.

Danger of bursting (explosion) when heated.

When using: development of explosive vapour/air mixture possible.

3.2 To the environment

See point 12.

4. First aid measures

4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007
Helmet & Visor Cleaner 500ml
Art.: 500107

4.3 Skin contact

Wash thoroughly with soap and water.
Remove contaminated clothing immediately.

4.4 Ingestion

Rinse the mouth thoroughly with water.
Consult doctor immediately - keep Data Sheet available.
Do not induce vomiting.

4.5 Special resources necessary for first aid

n.c.

5. Fire-fighting measures

5.1 Suitable extinguishing media

Foam
Dry extinguisher
CO₂

Cool container at risk with water.

5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon
Explosive vapour/air mixture
Danger of bursting (explosion) when heated.

5.4 Special protective equipment for fire-fighters

According to size of fire
Protective respirator with independent air supply

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid contact with eyes.
Avoid inhaling.

6.2 Environmental measures

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

6.3 Methods for cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. Handling and storage

7.1 Handling

Tips for safe handling:

See point 6.1
Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Do not use on hot surfaces.
Take measures against electrostatic charging, if appropriate.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.2. Storage

3 / 7

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007
 Helmet & Visor Cleaner 500ml
 Art.: 500107

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.
 Observe special regulations for aerosols.

Special storage conditions:

See point 10.2
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.

8. Exposure controls/personal protection

Chemical Name	Ammonia		
WEL-TWA: NH3 25 ppm (18 mg/m3) (WEL), 20 ppm (14 mg/m3) (EC)	WEL-STEL: NH3 35 ppm (25 mg/m3) (WEL), 50 ppm (36 mg/m3) (EC)	---	
BMGV: ---	Other information: ---		
Chemical Name	Ammonia		
WEL-TWA: NH3 25 ppm (18 mg/m3) (WEL), 20 ppm (14 mg/m3) (EC)	WEL-STEL: NH3 35 ppm (25 mg/m3) (WEL), 50 ppm (36 mg/m3) (EC)	---	
BMGV: ---	Other information: ---		
Chemical Name	Propan-2-ol		
WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---	
BMGV: ---	Other information: ---		
Chemical Name	Propan-2-ol		
WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---	
BMGV: ---	Other information: ---		
Chemical Name	Propane		
WEL-TWA: ---	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
Chemical Name	Isobutane		
WEL-TWA: ---	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period) | OELV-15min = Occupational Exposure Limit Value (15-minute reference period) | BLV = Biological limit value | Other information: C1, C2 = carcinogenic substance, Cat. 1 or 2. Mut 1, 2 = mutagenic substance, Cat. 1 or 2. Repr 1, 2 = Substances known to be toxic for reproduction, Cat. 1 or 2. Sk = can be absorbed through skin. Asphyx = asphyxiant. Sen = Respiratory sensitizer.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Respiratory protection: Normally not necessary.

If OES or MEL is exceeded.

Filter AX P3 (EN 141)

Hand protection: Normally not necessary.

Recommended

Protective nitrile gloves (EN 374)

Eye protection: Normally not necessary.

With danger of contact with eyes

Tight fitting protective goggles with side protection (EN 166).

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

GB

4 / 7

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007

Helmet & Visor Cleaner 500ml

Art.: 500107

Additional information on hand protection - No tests have been performed.
Selection made for preparations according to the best available knowledge and information on the ingredients.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

9. Physical and chemical properties

Physical state:	Aerosol
Propellant gas:	
Propane	
Isobutane	
Butane	
Colour:	Clear
Odour:	Characteristic
pH-value undiluted:	11
10 % pH-value:	10
Boiling point/range (°C):	n.av.
Melting point/range (°C):	n.av.
Flash point (°C):	< 21
Oxidising properties:	No
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.c.
Density (g/ml):	0,980, Active substance
Solubility in water:	Soluble
Viscosity:	5 mm ² /s (20°C)

10. Stability and reactivity

Conditions to avoid

See point 7

Stable when handled and stored correctly.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Materials to avoid

See point 7

Avoid contact with oxidizing agents.

Hazardous decomposition products

See point 5.3

11. Toxicological information

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

Further information

GB

5 / 7

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007

Helmet & Visor Cleaner 500ml

Art.: 500107

No classification according to calculation procedure.

The following may occur:

Irritation of the eyes

Irritation of the respiratory tract

12. Ecological information

Water hazard class (Germany):

1

Self classification:

Yes (Vw/vWS)

Persistence and degradability:

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

> 99,9% OECD 303A, (95% 21d mod. OECD-Screening-Test) *

Behaviour in sewage plants:

According to the recipe, contains no AOX.

Aquatic toxicity:

n.av.

Ecological toxicity:

n.av.

* Propan-2-ol

13. Disposal considerations

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

15 01 01 paper and cardboard packaging

15 01 04 metallic packaging

Return to manufacturer with residual pressure.

Do not perforate, cut up or weld uncleaned container.

14. Transport information

General statements

UN-Number:

1950

Road/Rail-transport (ADR/RID)

Class/packing-group:

2/-

UN 1950 AEROSOLS

Classification code:

5F

LQ:

2



Transport by sea

IMDG-code:

1950 (class/packing-group)

EmS:

F-D, S-U

Marine Pollutant:

n.a.

AEROSOLS



Transport by air

IATA:

2.1/-/ (class/secondary danger/packing-group)

Aerosols, flammable

Additional information:

Danger code and packing code on request.

15. Regulatory information

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007
Helmet & Visor Cleaner 500ml
Art.: 500107

Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)



Symbols: F+

Indications of danger:

Extremely flammable

R-phrases:

12 Extremely flammable.

Without adequate ventilation, formation of explosive mixtures may be possible.

S-phrases:

23.c Do not breathe spray.

35 This material and its container must be disposed of in a safe way.

51 Use only in well-ventilated areas.

Additions:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Observe restrictions:

Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

VOC 1999/13/EC 10,95% w/w

16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany):

2 B

Revised points:

2, 8, 12

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 2).

34 Causes burns.

50 Very toxic to aquatic organisms.

11 Highly flammable.

36 Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

Winzer Würth Industrial Lt.

Würth House

Catteshall Lane

GB - Godalming / Surrey

GU7 1NP

Tel: 01483 412800

Fax: 01483 412805

Würth Ireland Ltd.

Monaclinoe Industrial Estate

Ballysimon Road

GB - Limerick / Ireland

Tel: +353 61 430200

Fax: +353 61 430200

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference

period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.



GB

7 / 7

Revision: 19.02.2007 Replaces the version of: 12.11.2003 PDF date: 21.05.2007

Helmet & Visor Cleaner 500ml

Art.: 500107

These statements were made by:

**Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-
CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.