

1 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Identification of the substance or preparation

**Silicone Grease 300ml**

**Art.: 500124**

#### Use of the substance/preparation

Lubricant

#### Company/undertaking identification

Wurth UK Ltd 1 Centurion Way, Erith, UK-DA18 4AE Kent  
Telephone 020 8319 6000, Fax 020 8319 6400

Distributor: see point 16 of this EC safety data sheet

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

#### Emergency telephone

#### Advisory office in case of poisoning:

Tel.: +49 30 / 19240 Berlin

#### Telephone number of the company in case of emergencies:

Tel. 020 8319 6000 (08-00 h - 18-00 h)

### 2. HAZARDS IDENTIFICATION

#### To people

See point 11 and 15.

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

Product is extremely flammable.

Danger of bursting (explosion) when heated.

When using: development of explosive vapour/air mixture possible.

Irritation of the skin.

Vapours may cause drowsiness and dizziness

#### To the environment

See point 12.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Aerosol

| Chemical name                           |                            |                   |                |
|---|----------------------------|-------------------|----------------|
| content %                               | Symbol                     | R-phrases         | EINECS, ELINCS |
|   | Registration number (ECHA) | DNEL              | PNEC           |
| Naphtha (petroleum), hydrotreated light |                            |                   |                |
| 25 - 30                                 | F/Xn/Xi/N                  | 11-38-51-53-65-67 | 265-151-9      |
| Isobutane                               |                            |                   |                |
| 10 - 30                                 | F+                         | 12                | 200-857-2      |

GB

2 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

| Propane     |      |          |           |
|-------------|------|----------|-----------|
| 5 - 10      | F+   | 12       | 200-827-9 |
|             |      |          |           |
| Butane      |      |          |           |
| 1 - 5       | F+   | 12       | 203-448-7 |
|             |      |          |           |
| Propan-2-ol |      |          |           |
| 10 - 15     | F/Xi | 11-36-67 | 200-661-7 |
|             |      |          |           |
| Ethanol     |      |          |           |
| 1 - 5       | F    | 11       | 200-578-6 |
|             |      |          |           |

For complete wording of the R-phrases, refer to point 16.

## 4. FIRST AID MEASURES

### 4.1 Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

### 4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.  
Keep Data Sheet available.

### 4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

### 4.4 Ingestion

Rinse the mouth thoroughly with water.  
Call doctor immediately - have Data Sheet available.  
Do not induce vomiting.

### 4.5 Special resources necessary for first aid

n.c.

## 5. FIRE-FIGHTING MEASURES

### 5.1 Suitable extinguishing media

Water jet spray  
CO2  
Extinguishing powder  
Foam  
Cool container at risk with water.

### 5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

### 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:  
Oxides of carbon  
Toxic pyrolysis products.  
Danger of explosion by prolonged heating.  
Explosive vapour/air mixture  
In case of spreading near the ground, flashback to distance sources of ignition is possible.

### 5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply  
According to size of fire  
Full protection, if necessary

### 5.5 Further information

Dispose of contaminated extinction water according to official regulations.

(GB)

3 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
 Silicone Grease 300ml Art.: 500124

## 6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

### 6.1 Personal precautions

Remove possible causes of ignition - do not smoke.  
 Ensure sufficient supply of air.  
 Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
 Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods for cleaning up

If spray or gas escapes, ensure ample fresh air is available.  
 Active substance:  
 Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

## 7. HANDLING AND STORAGE

### 7.1 Handling

#### Tips for safe handling:

See point 6.1  
 Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Wash hands before breaks and at end of work.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.2. Storage

#### Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Observe special regulations for aerosols.

#### Special storage conditions:

See point 10  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure limit values

|       |                           |   |                   |
|-------|---------------------------|---|-------------------|
| (GB)  | <b>Chemical Name</b>      | Naphtha (petroleum), hydrotreated light | Content %:25 - 30 |
|       | WEL-TWA: 700 mg/m3 (AGW)  | WEL-STEL: 4(II) (AGW)                   | ---               |
|       | BMGV: ---                 | Other information: ---                  |                   |
| (IRL) | <b>Chemical Name</b>      | Naphtha (petroleum), hydrotreated light | Content %:25 - 30 |
|       | WEL-TWA: 700 mg/m3 (AGW)  | WEL-STEL: 4(II) (AGW)                   | ---               |
|       | BMGV: ---                 | Other information: ---                  |                   |
| (GB)  | <b>Chemical Name</b>      | Isobutane                               | Content %:10 - 30 |
|       | WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: ---                           | ---               |
|       | BMGV: ---                 | Other information: ---                  |                   |
| (IRL) | <b>Chemical Name</b>      | Isobutane                               | Content %:10 - 30 |
|       | WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: ---                           | ---               |

4 / 8

 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
 Silicone Grease 300ml Art.: 500124

|   |   |                   |
|---|---|-------------------|
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Propane                                     | Content %:5 - 10  |
| WEL-TWA: 1000 ppm (ACGIH)                   | WEL-STEL: ---                               | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Propane                                     | Content %:5 - 10  |
| WEL-TWA: 1000 ppm (ACGIH)                   | WEL-STEL: ---                               | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Butane                                      | Content %:1 - 5   |
| WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )  | WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> ) | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Butane                                      | Content %:1 - 5   |
| WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )  | WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> ) | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Propan-2-ol                                 | Content %:10 - 15 |
| WEL-TWA: 400 ppm (999 mg/m <sup>3</sup> )   | WEL-STEL: 500 ppm (1250 mg/m <sup>3</sup> ) | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Propan-2-ol                                 | Content %:10 - 15 |
| WEL-TWA: 400 ppm (999 mg/m <sup>3</sup> )   | WEL-STEL: 500 ppm (1250 mg/m <sup>3</sup> ) | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Ethanol                                     | Content %:1 - 5   |
| WEL-TWA: 1000 ppm (1920 mg/m <sup>3</sup> ) | WEL-STEL: ---                               | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |
| <b>Chemical Name</b>                        | Ethanol                                     | Content %:1 - 5   |
| WEL-TWA: 1000 ppm (1920 mg/m <sup>3</sup> ) | WEL-STEL: ---                               | ---               |
| BMGV: ---                                   | Other information: ---                      |                   |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period) | OELV-15min = Occupational Exposure Limit Value (15-minute reference period) | BLV = Biological limit value | Other information: C1, C2 = carcinogenic substance, Cat. 1 or 2. Mut 1, 2 = mutagenic substance, Cat. 1 or 2. Repro 1, 2 = Substances known to be toxic for reproduction, Cat. 1 or 2. Sk = can be absorbed through skin. Asphyx = asphyxiant. Sen = Respiratory sensitizer.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 141)

Gas mask filter AX (EN 141).

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

5 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

Protective nitrile gloves (EN 374)  
Protective hand cream recommended.

Eye protection:

Tight fitting protective goggles (EN 166) with side protection,  
with danger of projections.

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-  
sleeved protective working garments)

Additional information on hand protection - No tests have been performed.  
Selection made for preparations according to the best available knowledge and information on the ingredients.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates  
and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics  
and varies from manufacturer to manufacturer.  
In the case of preparations the resistance of glove materials cannot be calculated in advance  
so it has to be tested before use. The exact breakthrough time of the glove material can be  
requested from the protective glove manufacturer and must be observed.

### 8.2.2 Environmental exposure controls

n.av.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                   |                  |
|-----------------------------------|------------------|
| Physical state:                   | Aerosol          |
| Substance:                        | Liquid           |
| Colour:                           | n.av.            |
| Odour:                            | Characteristic   |
| pH-value undiluted:               | n.av.            |
| Boiling point/boiling range (°C): | n.av.            |
| Melting point/melting range (°C): | n.av.            |
| Flash point (°C):                 | n.a.             |
| Oxidising properties:             | No               |
| Minimum limit of explosion:       | 0,8 Vol%         |
| Maximum limit of explosion:       | 12,0 Vol%        |
| Vapour pressure:                  | 3400 mbar (20°C) |
| Density (g/ml):                   | n.c.             |
| Water solubility:                 | Insoluble        |
| Viscosity:                        | n.a.             |

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

See point 7  
Stable when handled and stored correctly.  
Pressure increase will result in danger of bursting.  
Heating, open flame, ignition sources

### Materials to avoid

See point 7  
Avoid contact with oxidizing agents.

### Hazardous decomposition products

See point 5.3

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity and immediate effects

|  |                  |
|--|------------------|
| Ingestion, LD50 rat oral (mg/kg):      | n.av.            |
| Inhalation, LC50 rat inhal.(mg/l/4h):  | n.av.            |
| Skin contact, LD50 rat dermal (mg/kg): | k.D.v., Irritant |
| Eye contact:                           | n.av.            |

### Delayed and chronic effects

|                |      |
|----------------|------|
| Sensitization: | n.c. |
|----------------|------|

GB

6 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

|                        |          |
|------------------------|----------|
| Carcinogenicity:       | n.c.     |
| Mutagenicity:          | n.c.     |
| Reproductive toxicity: | n.c.     |
| Narcosis:              | Possible |

### Further information

Classification according to calculation procedure.

The following may occur:

Irritation of the eyes

Product removes fat

Drying of the skin.

Skin resorption

Effects/damages the central nervous system

Inhalation:

Dizziness

Headaches

Effects/damages the central nervous system

Ingestion:

Irritation of the mouth and throat

Irritation of the stomach

## 12. ECOLOGICAL INFORMATION

|  |                |
|--|----------------|
| Water hazard class (Germany):                            | Not classified |
| Self classification:                                     | n.a.           |
| Persistence and degradability:                           |                |
| Not biodegradable *                                      |                |
| > 99.9% OECD 303A, (95% 21d mod. OECD-Screening-Test) ** |                |
| 94% (mod. OECD-Screening-Test) ***                       |                |
| Behaviour in sewage plants:                              |                |
| According to the recipe, contains no AOX.                |                |
| Aquatic toxicity:  | n.av.          |
| Ecological toxicity:                                     | n.av.          |
| * Naphtha (petroleum), hydrotreated light                |                |
| ** Propan-2-ol   |                |
| *** Ethanol  |                |

## 13. DISPOSAL CONSIDERATIONS

### 13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

### 13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Recommendation:

Do not perforate, cut up or weld uncleaned container.

## 14. TRANSPORT INFORMATION

### General statements

UN-Number: 1950

### Road/Rail-transport (ADR/RID)

Class/packing group: 2/-

UN 1950 AEROSOLS



GB

7 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

Classification code: 5F  
LQ: 2

**Transport by sea**

IMDG-code: 2.1/- (class/packing group)  
EmS: F-D, S-U  
Marine Pollutant: n.a.



AEROSOLS

**Transport by air**

IATA: 2.1/-/ (class/secondary danger/packing group)  
Aerosols, flammable

**Additional information:**

Danger code and packing code on request.

**15. REGULATORY INFORMATION****Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)**

Symbols: F+/Xi/N

Indications of danger: Extremely flammable

Irritant

Dangerous for the environment

R-phrases:

12 Extremely flammable.

Without adequate ventilation, formation of explosive mixtures may be possible.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

23.f Do not breathe vapour/spray.

24 Avoid contact with skin.

29/35 Do not empty into drains; dispose of this material and its container in a safe way.

51 Use only in well-ventilated areas.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Additions:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Observe restrictions: Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

VOC 1999/13/EC 94,25% w/w

**16. OTHER INFORMATION**

These details refer to the product as it is delivered.

Storage class VCI (Germany): 2 B

Revised points: 1 - 16 (REACH)

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 3).

11 Highly flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

65 Also harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

12 Extremely flammable.

36 Irritating to eyes.

GB

8 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 25.06.2008 Replaces the version of: 10.03.2004 PDF date: 25.06.2008  
Silicone Grease 300ml Art.: 500124

Winzer Würth Industrial Lt.  
Würth House  
Catteshall Lane  
GB - Godalming / Surrey  
GU7 1NP  
Tel: 01483 412800  
Fax: 01483 412805

Würth Ireland Ltd.  
Monaclinoe Industrial Estate  
Ballysimon Road  
GB - Limerick / Ireland  
Tel: +353 61 430200  
Fax: +353 61 430200

### Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40  
AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)  
VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.